

A New Linear Logic for Deadlock-Free Session-Typed Processes (Talk Abstract)*

Ornela Dardha
School of Computing Science
University of Glasgow
United Kingdom
Ornela.Dardha@glasgow.ac.uk

Simon J. Gay
School of Computing Science
University of Glasgow
United Kingdom
Simon.Gay@glasgow.ac.uk

Abstract

We propose a new type system for deadlock-free session-typed π -calculus, a core concurrent programming language, by integrating for the *first* time, two separate lines of work. The first is the *propositions-as-types* approach by Caires and Pfenning, which provides a linear logic foundation for session types and guarantees deadlock-freedom. The second is Kobayashi's approach in which types are annotated with *priorities* for detecting cyclic dependencies between communication operations. The outcome is a new and more expressive variant of classical linear logic with a proof assignment that gives a session type system with Kobayashi-style priorities.

CCS Concepts • **Software and its engineering** → **General programming languages**; *Formal Methods*; • **Theory of Computation** → *Concurrency*; *Logic*;

Keywords classical linear logic, session types, Curry-Howard

ACM Reference Format:

Ornela Dardha and Simon J. Gay. 2018. A New Linear Logic for Deadlock-Free Session-Typed Processes (Talk Abstract). In *Proceedings of Women in Logic Workshop (WiL2018)*. ACM, New York, NY, USA, 1 page. <https://doi.org/>

Background and Contribution

The Curry-Howard correspondence, or *propositions-as-types* paradigm, provides a canonical logical foundation for *functional* programming. With the discovery of linear logic [4], it was natural to ask for a similar account of *concurrent* programming. There have been attempts to relate the π -calculus [6] to classical linear logic [1], without resulting in a convincing Curry-Howard correspondence for concurrency.

Meanwhile, Honda *et al.* [7] developed *session types* as a formalism to statically check communication protocols in the π -calculus. Caires and Pfenning [2] discovered a Curry-Howard correspondence between intuitionistic linear logic and π -calculus with session types [7]. Wadler [8] introduced

CP, as an alternative formulation based on classical linear logic. The Caires-Pfenning approach gives a propositions-as-types theory of concurrent programming, and a logical foundation for session types. The type system guarantees deadlock-freedom by *forbidding* cyclic process structures.

However, rejecting cyclic process structures is strict: they are a *necessary*, but not *sufficient*, condition for the existence of deadlocked communication operations. Our contribution [3] is to define a new linear logic, *priority-based linear logic* (PLL), and formulate it as a session type system for *priority-based CP* (PCP), a more expressive class of session-typed π -calculus processes than Wadler's CP [8].

This is the *first Curry-Howard correspondence that allows cyclic interconnected processes, while still ensuring deadlock-freedom*. PLL is based on Kobayashi's type system [5] in which types are annotated with *priorities*. Priorities are natural numbers used to express conditions on inter-channel dependencies and detect deadlocks. On the technical results, we prove *CYCLE*-elimination for PLL, analogous to the standard *CUT*-elimination for CLL. *CYCLE*-elimination implies subject reduction, top-level deadlock-freedom, and full deadlock-freedom for closed processes for PCP. To conclude, our work can be viewed in three ways: (i) as a new linear logic in which cyclic proof structures can be derived; (ii) as an extension of Caires-Pfenning type systems so that they accept more processes, while maintaining the strong logical foundation; (iii) as a logical foundation for Kobayashi-style type systems.

References

- [1] Gianluigi Bellin and Philip J. Scott. 1994. On the π -Calculus and Linear Logic. *Theoretical Computer Science* 135, 1 (1994), 11–65.
- [2] Luis Caires and Frank Pfenning. 2010. Session Types as Intuitionistic Linear Propositions. In *CONCUR (LNCS)*, Vol. 6269. Springer, 222–236.
- [3] Ornela Dardha and Simon J. Gay. 2018. A New Linear Logic for Deadlock-Free Session-Typed Processes. In *FOSSACS (LNCS)*, Vol. 10803. Springer, 91–109. https://doi.org/10.1007/978-3-319-89366-2_5
- [4] Jean-Yves Girard. 1987. Linear Logic. *Theoretical Computer Science* 50 (1987), 1–102.
- [5] Naoki Kobayashi. 2006. A New Type System for Deadlock-Free Processes. In *CONCUR (LNCS)*, Vol. 4137. Springer, 233–247.
- [6] Davide Sangiorgi and David Walker. 2001. *The π -calculus: a Theory of Mobile Processes*. Cambridge University Press.
- [7] Kaku Takeuchi, Kohei Honda, and Makoto Kubo. 1994. An Interaction-Based Language and its Typing System. In *PARLE '94 (LNCS)*, Vol. 817. Springer, 398–413.
- [8] Philip Wadler. 2012. Propositions as sessions. In *ICFP*. ACM, 273–286.

*Supported by the UK EPSRC grant EP/K034413/1, “From Data Types to Session Types: A Basis for Concurrency and Distribution (ABCD)”, and by COST Action IC1201, “Behavioural Types for Reliable Large-Scale Software Systems (BETTY)”.